## NSN 4330-01-516-8422

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-516-8422

## Body Length:

4.9375 inches

## **Body Height:**

12.9375 inches

## Filtration Rating In Microns:

0.01

## End Application:

Ablts

#### Design Type:

Reusable

#### **Tempurature Rating:**

Between 35.0 degrees fahrenheit and 225.0 degrees fahrenheit

#### Filtering Element Quantity:

1

#### Maximum Operating Pressure:

250.0 pounds per square inch

#### Filtering Media Design:

Any acceptable single filtering media response

#### First Intake Connection Type:

Threaded external pipe top side

## First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

## First Intake Thread Series Designator:

Npt

## First Discharge Thread Series Designator:

Npt

#### First Intake Thread Size:

1.000 inches

## First Discharge Thread Size:

1.000 inches

#### Product Name:

Filter housing

#### First Intake Thread Direction:

Right-hand

## First Discharge Thread Direction:

**Right-hand** 

## **Special Features:**

Housings are made of cast aluminum and finished with an epoxy powder coating for corrosion resistance; filter has a float drain feature and also includes a differential pressure indicator kit; application: oil removal (liquids); element purpose: high efficiency coalescing; max. Inlet temperature: 125 degrees f; element flow direction: in/out

## Material:

Aluminum body

Media For Which Designed:

Fuel/oil, hydrocarbon

# NSN 4330-01-516-8422

Fluid Filter - Page 2 of 2

Style Designator:

Straight flow basket strainer w/ bolted cover

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A24000

