## NSN 4330-01-516-8422



Fluid Filter - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4330-01-516-8422 **Body Length:** 4.9375 inches **Body Height:** 12.9375 inches **Filtration Rating In Microns:** 0.01 **End Application:** Ablts **Design Type:** Reusable **Tempurature Rating:** Between 35.0 degrees fahrenheit and 225.0 degrees fahrenheit **Filtering Element Quantity:** 1 **Maximum Operating Pressure:** 250.0 pounds per square inch Filtering Media Design: Any acceptable single filtering media response First Intake Connection Type: Threaded external pipe top side First Discharge Connection Relationship To Intake Connection: Identical to first intake connection First Intake Thread Series Designator: Npt First Discharge Thread Series Designator: Npt First Intake Thread Size: 1.000 inches First Discharge Thread Size: 1.000 inches **Product Name:** Filter housing **First Intake Thread Direction:** Right-hand **First Discharge Thread Direction:** Right-hand **Special Features:** 

Housings are made of cast aluminum and finished with an epoxy powder coating for corrosion resistance; filter has a float drain feature and also includes a differential pressure indicator kit; application: oil removal (liquids); element purpose: high efficiency coalescing; max. Inlet temperature: 125 degrees f; element flow direction: in/out

Material:

Aluminum body

Media For Which Designed:

Fuel/oil, hydrocarbon

## NSN 4330-01-516-8422

Fluid Filter - Page 2 of 2



Style	e Des	ignator	'
Style	e Des	ignator	'

Straight flow basket strainer w/ bolted cover

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A24000