## NSN 4330-01-523-9087

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-523-9087

Mounting Type:
Unthreaded hole top
Mounting Hole Diameter:
0.295 inches
Mounting Hole Quantity:
4
Body Outside Diameter:
4.960 inches
Body Height:
8.180 inches
Filtration Rating In Microns:
10.0 absolute
Distance Between Mounting Hole Centers:
4.960 inches
End Application:
Alofts sonar system, model 980 (v1)
Design Type:
Nonreusable
Tempurature Rating:
Between -40.0 degrees celsius and 121.0 degrees celsius
Filtering Element Quantity:
1
Maximum Operating Pressure:
360.0 pounds per square inch
First Intake Connection Type:
Threaded internal pipe side
First Discharge Connection Relationship To Intake Connection:
Not identical
First Discharge Connection Type:
Threaded internal pipe bottom
First Intake Thread Series Designator:
Un
First Discharge Thread Series Designator:
Un
First Intake Thread Size:
1.625 inches
First Discharge Thread Size:
1.625 inches
First Intake Thready Qty Per Inch (tpi):
12
First Discharge Thready Qty Per Inch (tpi):

## **NSN 4330-01-523-9087** Fluid Filter - Page 2 of 2



First Intake Thread Class:
2b
First Discharge Thread Class:
2b
Product Name:
Filter assembly, hydraulic, housing with element
First Intake Thread Direction:
Right-hand
First Discharge Thread Direction:
Right-hand
Filtering System For Which Designed:
By-pass flow
Material:
Rubber buna n seal
Media For Which Designed:
Fuel/oil, hydrocarbon
Style Designator:
Ell type (hydraulic)
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A24000