## NSN 4330-01-523-9087

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-01-523-9087

| Mounting Type:  |
|---|
| Unthreaded hole top   |
| Mounting Hole Diameter:                                       |
| 0.295 inches  |
| Mounting Hole Quantity:                                       |
| 4   |
| Body Outside Diameter:  |
| 4.960 inches  |
| Body Height:  |
| 8.180 inches  |
| Filtration Rating In Microns:                                 |
| 10.0 absolute   |
| Distance Between Mounting Hole Centers:                       |
| 4.960 inches  |
| End Application:  |
| Alofts sonar system, model 980 (v1)                           |
| Design Type:  |
| Nonreusable   |
| Tempurature Rating:   |
| Between -40.0 degrees celsius and 121.0 degrees celsius       |
| Filtering Element Quantity:                                   |
| 1   |
| Maximum Operating Pressure:                                   |
| 360.0 pounds per square inch                                  |
| First Intake Connection Type:                                 |
| Threaded internal pipe side                                   |
| First Discharge Connection Relationship To Intake Connection: |
| Not identical   |
| First Discharge Connection Type:                              |
| Threaded internal pipe bottom                                 |
| First Intake Thread Series Designator:                        |
| Un  |
| First Discharge Thread Series Designator:                     |
| Un  |
| First Intake Thread Size:                                     |
| 1.625 inches  |
| First Discharge Thread Size:                                  |
| 1.625 inches  |
| First Intake Thready Qty Per Inch (tpi):                      |
| 12  |
| First Discharge Thready Qty Per Inch (tpi):                   |

## **NSN 4330-01-523-9087** Fluid Filter - Page 2 of 2



| First Intake Thread Class:                       |
|--|
| 2b   |
| First Discharge Thread Class:                    |
| 2b   |
| Product Name:                                    |
| Filter assembly, hydraulic, housing with element |
| First Intake Thread Direction:                   |
| Right-hand                                       |
| First Discharge Thread Direction:                |
| Right-hand                                       |
| Filtering System For Which Designed:             |
| By-pass flow                                     |
| Material:  |
| Rubber buna n seal                               |
| Media For Which Designed:                        |
| Fuel/oil, hydrocarbon                            |
| Style Designator:                                |
| Ell type (hydraulic)                             |
| Shelf Life:                                      |
| N/a  |
| Unit Of Measure:                                 |
|  |
| Demilitarization:                                |
| No   |
| Fiig:  |
| A24000   |
|  |