

View Online at <https://aerobasegroup.com/nsn/4410-01-505-0893>

**Current Type:**

Dc

**Frequency Rating:**

Between 50.0 hertz and 60.0 hertz

**Voltage Rating:**

480.0 volts

**Horsepower Rating:**

1.8

**Draft Type:**

Natural

**Mounting Method:**

Floor

**Maximum Operating Pressure:**

80.0 pounds per square inch gage

**Steam Capacity:**

Between 36.000 pounds per hour and 543.000 pounds per hour

**Waterwalls:**

Not provided

**Forced Circulation Feature:**

Not provided

**Ignition Method:**

Electrical

**Marine Service Design Feature:**

Not provided

**Maintenance Parts:**

Not provided

**Packaged Boiler:**

Not provided

**Superheater:**

Not provided

**Special Features:**

6 bolt flanged heating element; 0.438 in. Mounting hole in each leg of floor mount; no superheater; no draft type; no packaged boiler; no igniter, the boiler is electric heated; 90 psig working pressure, although it is recommended at 80 - 83 psig max. Working pressure; relief valve set at 100 psig; 22 amps; 120 volts control circuit; 480 volts power circuit voltage; 1.8 boiler horse power

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T242-a