NSN 4510-00-516-4677

Flush Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4510-00-516-4677

Brass Outside Surface Treatment: Chromium Body Style: Flush valve (enclosed type) Stem Material: Brass Media For Which Designed: Water, freah First End Connection Type: Threaded external pipe First End Onnection Type: Threaded external pipe First End Style Designator: Plain Direct End Style Designator: Plain Brist End Pipe Size Accommodated: 0.500 inches First End Thread Direction: Righ-hand Second End Relationship With First End: Identical Intel Location: Brask Second End Relationship With First End: Identical Vage Design: Concealed pipe Flow Control Device Material: Brass Valve Deparation Method: Push button End Connection Quantity: 2 Portating Mechanism Angle From Intel In Deg: 180.0 Piersure Pressure	Body Material:	
Outside Surface Treatment: Chromium Bod Style: Flush valve (enclosed type) Stem Material: Brass Media For Which Designed: Water, fresh First End Connection Type: Threaded external pipe First End Style Designator: Plain Scoti Inde State Accommodated: 0:500 Inches First End Pipe State Accommodated: 0:500 Inches Brask Second End Relationship With First End: Identication: Brask Second End Relationship With First End: Ident Location: Brask Second End Relationship Mich End Edd Edd Edd Edd Edd Edd Edd Edd Edd		
Chromium Body Style: Flush valve (enclosed type) Stem Material: Brass Modia For Which Designed: Water, fresh First End Connection Type: Threade external pipe First End Style Designator: Plain First End Pipe Size Accommodated: 0.500 inches First End Thread Direction: Right-hand Second End Relationship With First End: Identical Intel Location: Back Second End Relationship With First End: Identical Intel Location: Back Second End Relationship With First End: Identical Identical Prestore: Usage Design: Conconclud pipe Flow Control Device Material: Brass Valve Operation Method: Pressure Valve Operation Method: Pressure Parating Mechanism Angle From Inlet In Deg: 180:0 Fluestrip: Pressure <		
Floady style: Floady valves (enclosed type) Sterm Material: Brass Media For Which Designed: Valuer, fresh First End Connection Type: Threaded external pipe First End Style Designator: Plain First End Pipe Size Accommodated: 0.500 inches First End Thread Direction: Right-hand Socon End Relationship With First End: Identical Intel Location: Back Sead Material: Concealed pipe Floady Control Device: Daphragm Fload Connection Quantity: Parse Valve Operation Method: Push button End Connection Quantity: 12 Pressure Staoutity: 130.0 Floading Control Relationshing From Intel th Deg: 130.0 Floading Control Standard: Pressure Standing Control Relation Contro		
Flush valve (enclosed type) Stem Material: Brass Media For Which Designed: Water, fresh First End Connection Type: Threaded external pipe First End Style Designator: Plain Staten These Direction: Right-hand Second End Relationship With First End: Idential Intel Location: Back Second End Relationship With First End: Idential Intel Location: Back Second End Relationship With First End: Idential Intel Location: Back Second End Relationship With First End: Idential Intel Location: Back Second End Relationship With First End: Idential Intel Location: Back Second End Relationship With First End: Idential Intel Location: Back Second End Relationship Mather Intel Location: Back Secontrol Device Material:		
Stem Material:BrassMedia For Which Designed:Water, freshFirst End Connection Type:Threaded external pipeFirst End Style Designator:PlainFirst End Pipe Size Accommodated:0.500 inchesFirst End Thread Direction:Right-handSecond End Relationship With First End:IdenticalInlet Location:BackSeade sternal pipeConcealed pipeFirst End Direction:BrassConcealed pipeFor Control Device:DiaphragmFlow Control Device Material:BrassValve Operation Method:Push buttonBrassPland Direction:BrassFlow Control Device Material:BrassPland Direction:BrassFlow Control Device Material:BrassPland Direction:BrassPland Direction:BrassPland Direction Quantity:2Specification Of Standard:PressureSpecification Of Standard:Expand 3 type and 2 style and d modelSheft Life:		
Brass Media For Which Designed: Water, fresh First End Connection Type: Threaded external pipe First End Style Designator: Plain First End Type Designator: 0.500 inches First End Thread Direction: Right-hand Second End Relationship With First End: Identical Intel Location: Back Second End Relationship With First End: Identical Intel Location: Back Second End Relationship With First End: Identical Intel Location: Back Second End Relationship With First End: Identical Intel Location: Back Second End Relationship With First End: Identical Intel Location: Back Second End Relationship With First End: Identical Intel Location: Concealed pipe Flow Control Device: Iophargam Flow Control Device Material: Iophargam		
Water, fresh First End Connection Type: Threaded external pipe First End Style Designator: Plain First End Pipe Size Accommodated: 0.500 inches First End Thread Direction: Right-hand Second End Relationship With First End: Identical Intel Location: Back Seat Material: Brass Usage Design: Concealed pipe Flow Control Device: Diaphragm Flow Control Device: Diaphragm Flow Control Device Material: Brass Valve Operation Method: Push button End Connection Quantity: 2 Porating Mechanism Angle From Inlet In Deg: 18:00 Flow Style Pressure Specification Or Standard: Experimetion Standard:<		
Water, fresh First End Connection Type: Threaded external pipe First End Style Designator: Plain First End Pipe Size Accommodated: 0.500 inches First End Thread Direction: Right-hand Second End Relationship With First End: Identical Intel Location: Back Seat Material: Drace Direction Concealed pipe Flow Control Device: Diaphragm Flow Control Device Diaphragm Flow Control Device Material: Prass Valve Operation Method: Push button Parating Mechanism Angle From Inlet In Deg: 1800 Flow Instrume 1800 Flow Entries Parating Mechanism Angle From Inlet In Deg: 1800 Flow Entries 1800 Flow Entries 1800 Flow Entries Parating Mechanism Angle From Inlet In Deg: 1800 Flow Entries Pressure		
First End Connection Type: Threaded external pipe First End Style Designator: Plain First End Pipe Size Accommodated: 0.500 inches First End Thread Direction: Right-hand Second End Relationship With First End: Identical Intel Location: Back Second End Relationship With First End: Identical Intel Location: Back Second End Relationship With First End: Identical Intel Location: Back Second End Relationship With First End: Identical Intel Location: Back Second End Relationship With First End: Back Second End Relationship With First End: Back Seconder Delation: Back Second End Relationship Material: Back Vance Ontrol Device: Ibarbarg Post Device: Ibarbarg Post Device: Post End Mechanism Angle From Inlet In Deg: Ibarbar		
Threaded external pipe First End Style Designator: Plain First End Pipe Size Accommodated: 0.500 inches First End Thread Direction: Right-hand Second End Relationship With First End: Identical Inter Location: Back Seat Material: Concealed pipe First Source Material: Diaphragm Fow Control Device: Diaphragm Flack Parase Valve Operation Method: Pass Valve Operation Method: Pass Pass Valve Operation Method: Pass Pass Pass Valve Operation Method: Pass Pass <t< td=""><td></td><td></td></t<>		
First End Style Designator: Plain First End Pipe Size Accommodated: 0.500 inches First End Thread Direction: Right-hand Second End Relationship With First End: Identical Inlet Location: Back Seat Material: Brass Usage Design: Concealed pipe Flow Control Device: Diaphragm Flow Control Device: Parass Valve Operation Method: Post Post Entition State Section Method: Prass Valve Operation Method: Post Control Device Material: Prass Valve Operation Method: Post Control Device Material: Prass Valve Operation Method: Post Control Device Material: Prass Post Control Device Material: Prass Post Control Device Material: Prass Post Control Device Material: Post Control Device Material: Post Control Device Material: <		
Plain First End Pipe Size Accommodated: 0.500 inches First End Thread Direction: Right-hand Second End Relationship With First End: Identical Inlet Location: Back Sect Material: Barss Usage Design: Concealed pipe Flow Control Device: Diaphragm Flow Control Device Material: Brass Valve Operation Method: Push button End Connection Quantity: 12 Pressure Pressure Specification Of Standard: E part and 3 type and 2 style and d model Sheff Life:		
First End Pipe Size Accommodated: 0.500 inches First End Thread Direction: Right-hand Second End Relationship With First End: Identical Inlet Location: Back Seat Material: Brass Usage Design: Concealed pipe Flow Control Device: Diaphragm Flow Control Device Material: Brass Valve Operation Method: Push button End Connection Quantity: 12 Pissure Pissure Flow Type: Pissure Pissure Pissure Flow Type and 2 style and d model Shift Life:		
0.500 inches First End Thread Direction: Right-hand Second End Relationship With First End: Identical Intel Location: Back Seat Material: Brass Usage Design: Concealed pipe Flow Control Device: Diaphragm Flow Control Device Material: Brass Valve Operation Method: Push button End Connection Quantity: 2 Operating Mechanism Angle From Inlet In Deg: 180.0 Flush Type: Pressure Specification Or Standard: E part and 3 type and 2 style and d model Shelf Life:		
First End Thread Direction: Right-hand Second End Relationship With First End: Identical Intel Location: Back Seat Material: Brass Usage Design: Concealed pipe Flow Control Device: Diaphragm Flow Control Device Material: Brass Valve Operation Method: Push button Brass Push Device Material: Push Dutton End Connection Quantity: 10.0 Fush Type: Pressure Pusheut Push Dutton End Connection Of Standard: E part and 3 type and 2 style and d model	-	
Right-hand Second End Relationship With First End: Identical Inlet Location: Back Back Seat Material: Brass Usage Design: Concealed pipe Flow Control Device: Diaphragm Flow Control Device Material: Brass Valve Operation Method: Push button Parton P		
Second End Relationship With First End:IdenticalInlet Location:BackSeat Material:BrassUsage Design:Concealed pipeFlow Control Device:DiaphragmFlow Control Device Material:BrassValve Operation Method:Push buttonEnd Connection Quantity:2Operating Mechanism Angle From Inlet In Deg:180.0Flush Type:PressureAperification Or Standard:E part and 3 type and 2 style and d modelShelf Life:		
IdenticalInlet Location:BackBackSeat Material:IransUsage Design:Concealed pipeFlow Control Device:DiaphragmFlow Control Device Material:BrassValve Operation Method:Push buttonEnd Connection Quantity:2Operating Mechanism Angle From Inlet In Deg:180.0Flush Type:PressureSpecification Of Standard:E part and 3 type and 2 style and d modelShelf Life:		d.
Inlet Location:BackBackSeat Material:BrassUsage Design:Concealed pipeFlow Control Device:DiaphragmFlow Control Device Material:BrassValve Operation Method:Push buttonEnd Connection Quantity:2Deprating Mechanism Angle From Inlet In Deg:180.0Flush Type:PressureSpecification Or Standard:E part and 3 type and 2 style and d modelShelf Life:		-
BackSeat Material:GrassUsage Design:Concealed pipeFlow Control Device:DiaphragmFlow Control Device Material:BrassValve Operation Method:Push buttonEnd Connection Quantity:2Operating Mechanism Angle From Inlet In Deg:180.0Flush Type:PressureSpecification Of Standard:E part and 3 type and 2 style and d modelShelf Life:		
Seat Material:BrassBrassUsage Design:Concealed pipeFlow Control Device:DiaphragmFlow Control Device Material:BrassValve Operation Method:Push buttonEnd Connection Quantity:2Operating Mechanism Angle From Inlet In Deg:180.0Flush Type:PressureSpecification Of Standard:E part and 3 type and 2 style and d modelShelf Life:		
BrassUsage Design:Concealed pipeFlow Control Device:DiaphragmFlow Control Device Material:BrassValve Operation Method:Push buttonEnd Connection Quantity:2Operating Mechanism Angle From Inlet In Deg:180.0Flush Type:PressureSpecification Of Standard:E part and 3 type and 2 style and d modelShelf Life:		
Concealed pipe Flow Control Device: Diaphragm Flow Control Device Material: Brass Valve Operation Method: Push button End Connection Quantity: 2 Operating Mechanism Angle From Inlet In Deg: 180.0 Flush Type: Pressure Specification Or Standard: E part and 3 type and 2 style and d model Shelf Life:		
Concealed pipe Flow Control Device: Diaphragm Flow Control Device Material: Brass Valve Operation Method: Push button End Connection Quantity: 2 Operating Mechanism Angle From Inlet In Deg: 180.0 Flush Type: Pressure Specification Or Standard: E part and 3 type and 2 style and d model Shelf Life:	Usage Design:	
Flow Control Device:DiaphragmFlow Control Device Material:BrassValve Operation Method:Push buttonEnd Connection Quantity:2Operating Mechanism Angle From Inlet In Deg:180.0Flush Type:PressureSpecification Or Standard:E part and 3 type and 2 style and d modelShelf Life:		
Flow Control Device Material:BrassValve Operation Method:Push buttonEnd Connection Quantity:2Operating Mechanism Angle From Inlet In Deg:180.0Flush Type:PressureSpecification Or Standard:E part and 3 type and 2 style and d modelShelf Life:		
Flow Control Device Material:BrassValve Operation Method:Push buttonEnd Connection Quantity:2Operating Mechanism Angle From Inlet In Deg:180.0Flush Type:PressureSpecification Or Standard:E part and 3 type and 2 style and d modelShelf Life:	Diaphragm	
BrassValve Operation Method:Push buttonEnd Connection Quantity:2Operating Mechanism Angle From Inlet In Deg:180.0Flush Type:PressureSpecification Or Standard:E part and 3 type and 2 style and d modelShelf Life:		
Valve Operation Method:Push buttonEnd Connection Quantity:2Operating Mechanism Angle From Inlet In Deg:180.0Flush Type:PressureSpecification Or Standard:E part and 3 type and 2 style and d modelShelf Life:	Brass	
Push buttonEnd Connection Quantity:2Operating Mechanism Angle From Inlet In Deg:180.0Flush Type:PressureSpecification Or Standard:E part and 3 type and 2 style and d modelShelf Life:	Valve Operation Method:	
2 Operating Mechanism Angle From Inlet In Deg: 180.0 Flush Type: Pressure Specification Or Standard: E part and 3 type and 2 style and d model Shelf Life:		
2 Operating Mechanism Angle From Inlet In Deg: 180.0 Flush Type: Pressure Specification Or Standard: E part and 3 type and 2 style and d model Shelf Life:	End Connection Quantity:	
180.0 Flush Type: Pressure Specification Or Standard: E part and 3 type and 2 style and d model Shelf Life:		
Flush Type: Pressure Specification Or Standard: E part and 3 type and 2 style and d model Shelf Life:	Operating Mechanism Angle From Inlet	In Deg:
Pressure Specification Or Standard: E part and 3 type and 2 style and d model Shelf Life:	180.0	
Specification Or Standard: E part and 3 type and 2 style and d model Shelf Life:	Flush Type:	
E part and 3 type and 2 style and d model Shelf Life:	Pressure	
Shelf Life:	Specification Or Standard:	
	E part and 3 type and 2 style and d model	
N/a	Shelf Life:	
	N/a	

NSN 4510-00-516-4677

Flush Valve - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A07100

