NSN 4510-01-468-1902



| Water Mixing Valve - Page 1 of 2 | | | | | |
|---|--|--|--|--|--|
| View Online at https://aerobasegroup.com/nsn/4510-01-468-1902 | | | | | |
| Body Material: | | | | | |
| Steel, corrosion resisting | | | | | |
| Maximum Operating Pressure: | | | | | |
| 45.0 pounds per square inch | | | | | |
| Body Style: | | | | | |
| Tee give "adql" and "adap" only of flanged both ends | | | | | |
| Tempurature Rating: | | | | | |
| 120.0 degrees fahrenheit | | | | | |
| First End Connection Type: | | | | | |
| Threaded internal tube | | | | | |
| First End Style Designator: | | | | | |
| Optional end | | | | | |
| First End Outside Diameter Tube Accommodated: | | | | | |
| 0.750 inches | | | | | |
| First End Thread Direction: | | | | | |
| Right-hand | | | | | |
| Second End Relationship With First End: | | | | | |
| Identical | | | | | |
| Second End Style Designator: | | | | | |
| Optional end | | | | | |
| Third End Relationship With Preceding Ends: | | | | | |
| Identical with first end | | | | | |
| Fourth End Style Designator: | | | | | |
| Optional end | | | | | |
| Usage Design: | | | | | |
| Exposed pipe | | | | | |
| Flow Control Device: | | | | | |
| Piston, spring loaded | | | | | |
| End Connection Quantity: | | | | | |
| 3 | | | | | |
| Valve Discharge Flow Rate: | | | | | |
| 5.0 gallons per minute | | | | | |
| | | | | | |

End Application:

Valve, tepm re; nimitz class cvn

First End Thread Series Designator:

Ptf-spl

First End Thread Size:

0.750 inches

Product Name:

Tempcontrol valve

Shelf Life:

N/a

NSN 4510-01-468-1902

Water Mixing Valve - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|-----|-----|------|
| In | 18 | <i>(</i>)+ | МЛО | 201 | ure: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A07100