NSN 4520-00-067-7572

Portable Duct Type Heater - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4520-00-067-7572 **Mounting Type:** Hand carry **Heat Medium Type:** Air **Heat Outlet Quantity: Heat Delivery Direction:** Horizontal **Heat Discharge Outlet Type:** Stationary **Heat Directing Device:** Flexible ducts Air Circulation Device: Squirrel cage blower **Speed Adjustments:** Single speed **Circulated Air Type:** Heated Air Filter Type: Replaceable preformed **Radio Interference Suppression Type:** Af, mil-std-826, radio suppression Width: 21.000 inches **Current Type:** Ac Depth: 15.000 inches **Prime Mover Type:** Diesel engine **Operating Control Type:** Hand switch **Current Rating In Amps:** 1.5 **Heating Element Type:** Burner **Ignition Method:** Manual **Inclosure Material:** Any acceptable **Heat Delivery Rate:** 100000.0 british thermal unit

NSN 4520-00-067-7572Portable Duct Type Heater - Page 2 of 2



| Fuel Feed Method: |
|--|
| External pressure |
| Voltage In Volts: |
| 220.0 and 440.0 |
| Phase: |
| Three |
| Frequency In Hertz: |
| 60.0 |
| Fuel Type: |
| Butane |
| Height: |
| 42.000 inches |
| Quantity: |
| 1 |
| Reference Data And Literature: |
| T.O. 35e7-6-9-1 |
| Surface Treatment: |
| Paint |
| Reference Number Differentiating Characteristics: |
| As modified by radio noise filteror as modified by ball joints on running gear |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A01300 |
| |