

View Online at <https://aerobasegroup.com/nsn/4520-00-096-2790>

Mounting Type:

Hand carry

Heat Medium Type:

Air

Heat Outlet Quantity:

1

Heat Delivery Direction:

Horizontal

Heat Discharge Outlet Type:

Stationary

Heat Directing Device:

Adjustable louver

Air Circulation Device:

Squirrel cage blower

Speed Adjustments:

Single speed

Maximum Air Flow Rate:

5350.0 cubic feet per minute

Circulated Air Type:

Heated

Air Filter Type:

Replaceable preformed

Flue Connection Location:

On upper right side

Width:

Any acceptable

Current Type:

Ac

Depth:

Any acceptable

Prime Mover Type:

Gasoline engine

Operating Control Type:

Automatic control switch

Current Rating In Amps:

Any acceptable

Heating Element Type:

Combustion chamber

Ignition Method:

Electrode

Inclosure Material:

Steel

Fuel Consumption Rate Per Hour:

4.5 gallons

Heat Delivery Rate:

500000.0 british thermal unit

Fuel Feed Method:

Internal pump

Voltage In Volts:

110.0 and 220.0

Phase:

Single

Frequency In Hertz:

60.0

Fuel Type:

Fs no. 2 burner fuel oil

Height:

Any acceptable

Quantity:

2

Surface Treatment:

Any acceptable

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A01300