

View Online at <https://aerobasegroup.com/nsn/4520-00-114-1055>

Mounting Type:

Floor surface, free standing, nonducted

Heat Medium Type:

Air

Air Circulation Device:

Propeller fan

Speed Adjustments:

Single speed

Maximum Air Flow Rate:

500.0 cubic feet per minute

Circulated Air Type:

Heated

Radio Interference Suppression Type:

Army, mil-std-461, radio suppression

Flue Connection Location:

On front side 4-3/16 in. From top, 9/16 to left of center

Width:

28.375 inches

Current Type:

Ac

Depth:

11.062 inches

Prime Mover Type:

Electric motor

Operating Control Type:

Thermostatic

Current Rating In Amps:

Any acceptable

Heating Element Type:

Combustion chamber

Ignition Method:

Electrode

Inclosure Material:

Any acceptable

Fuel Consumption Rate Per Hour:

1.333 gallons

Heat Delivery Rate:

60000.0 british thermal unit

Fuel Feed Method:

Gravity

Voltage In Volts:

120.0

Phase:

Single

Frequency In Hertz:

50.0 or 60.0

Fuel Type:

Jp-4 jet fuel and df-a arctic diesel fuel oil and df-1 winter diesel fuel oil

Height:

21.188 inches

Quantity:

1

Unpackaged Unit Weight:

120.00 pounds

Surface Treatment:

Paint

Surface Treatment Specification:

Mil-t-704, type a military specification single treatment response

Specification Data:

81349-mil-h-11511 government specification

Specification Or Standard:

1 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A01300

Mil-std (military Standard):

Mil-t-704 spec.