NSN 4520-00-450-9554

Mounting Type:Ceiling suspended

Steam-hot Water Air Circulating Unit Heater - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4520-00-450-9554

| Heat Medium Type: |
|----------------------------------|
| Hot water |
| Maximum Pressure Limit: |
| 80.0 pounds per square inch gage |
| Heat Outlet Quantity: |
| 1 |
| Heat Delivery Direction: |
| Vertical |
| Heat Discharge Outlet Type: |
| Stationary |
| Heat Directing Device: |
| Four cone diffuser |
| Air Circulation Device: |
| Propeller fan |
| Speed Adjustments: |
| Single speed |
| Maximum Air Flow Rate: |
| 2440.0 cubic feet per minute |
| Circulated Air Type: |
| Heated |
| Width: |
| 29.500 inches |
| Current Type: |
| Ac |
| Depth: |
| 29.500 inches |
| Prime Mover Type: |
| Electric motor |
| Operating Control Type: |
| Any acceptable |
| Current Rating In Amps: |
| 1.5 |
| Heating Element Type: |
| Hot water coil and steam coil |
| Inclosure Material: |
| Any acceptable |
| Heat Delivery Rate: |
| 152000.0 british thermal unit |
| Voltage In Volts: |
| 115.0 |

NSN 4520-00-450-9554

Steam-hot Water Air Circulating Unit Heater - Page 2 of 2



| Phase: |
|---------------------|
| Single |
| Frequency In Hertz: |
| 60.0 |
| Height: |
| 13.625 inches |
| Quantity: |
| 1 |
| Shelf Life: |
| N/a |
| |
| Unit Of Measure: |
| Unit Of Measure: |
| |

Fiig: A01300