

View Online at <https://aerobasegroup.com/nsn/4520-00-878-9393>

Mounting Type:

Hand carry

Heat Medium Type:

Air

Air Circulation Device:

Propeller fan

Speed Adjustments:

Single speed

Maximum Air Flow Rate:

115.0 cubic feet per minute

Circulated Air Type:

Heated

Radio Interference Suppression Type:

Army, mil-e-53301, radio suppression

Flue Connection Location:

On lower right rear 2.750 in. From bottom

Width:

12.000 inches

Current Type:

Dc

Depth:

13.000 inches

Prime Mover Type:

Electric motor

Operating Control Type:

Thermostatic

Current Rating In Amps:

12.0

Heating Element Type:

Combustion chamber

Ignition Method:

Electrode

Inclosure Material:

Steel

Fuel Consumption Rate Per Hour:

0.3 gallons

Heat Delivery Rate:

15000.0 british thermal unit

Fuel Feed Method:

Internal pump

Voltage In Volts:

24.0

Fuel Type:

Df-a arctic diesel fuel oil and df-1 winter diesel fuel oil and df-2 regular diesel fuel oil and 80/87 octane gasoline and 91/96 octane gasoline

Height:

12.000 inches

Quantity:

1

Surface Treatment:

Paint

Surface Treatment Specification:

Mil-t-704, type a military specification single treatment response

Specification Data:

81349-mil-h-52204 government specification

Specification Or Standard:

3 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A01300

Mil-std (military Standard):

Mil-t-704 spec.