

View Online at <https://aerobasegroup.com/nsn/4520-01-274-4707>

Mounting Type:

Ceiling suspended

Heat Medium Type:

Hot water or steam

Maximum Pressure Limit:

25.0 pounds per square inch gage

Heat Outlet Quantity:

1

Heat Delivery Direction:

Horizontal

Heat Discharge Outlet Type:

Adjustable

Heat Directing Device:

Adjustable louver

Air Circulation Device:

Propeller fan

Speed Adjustments:

Single speed

Maximum Air Flow Rate:

1330.0 cubic feet per minute

Circulated Air Type:

Heated

Width:

31.000 inches

Current Type:

Ac

Depth:

28.000 inches

Prime Mover Type:

Electric motor

Operating Control Type:

Any acceptable

Current Rating In Amps:

0.81

Heating Element Type:

Hot water coil and steam coil

Inclosure Material:

Steel

Heat Delivery Rate:

74500.0 british thermal unit

Voltage In Volts:

115.0

Phase:

Single

Special Features:

Metal is hot phosphoric acid treated and given 2 coats of primer before painted

Frequency In Hertz:

60.0

Height:

24.750 inches

Quantity:

1

Unpackaged Unit Weight:

191.00 pounds

Surface Treatment:

Enamel

Surface Treatment Specification:

Mil-e-15024, class 2 military specification single treatment response

Specification Data:

81349-mil-u-17293d government specification

Specification Or Standard:

1 type and 14 size

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A01300

Mil-std (military Standard):

Mil-e-15024 spec.