

View Online at <https://aerobasegroup.com/nsn/4520-01-274-4707>

**Mounting Type:**

Ceiling suspended

**Heat Medium Type:**

Hot water or steam

**Maximum Pressure Limit:**

25.0 pounds per square inch gage

**Heat Outlet Quantity:**

1

**Heat Delivery Direction:**

Horizontal

**Heat Discharge Outlet Type:**

Adjustable

**Heat Directing Device:**

Adjustable louver

**Air Circulation Device:**

Propeller fan

**Speed Adjustments:**

Single speed

**Maximum Air Flow Rate:**

1330.0 cubic feet per minute

**Circulated Air Type:**

Heated

**Width:**

31.000 inches

**Current Type:**

Ac

**Depth:**

28.000 inches

**Prime Mover Type:**

Electric motor

**Operating Control Type:**

Any acceptable

**Current Rating In Amps:**

0.81

**Heating Element Type:**

Hot water coil and steam coil

**Inclosure Material:**

Steel

**Heat Delivery Rate:**

74500.0 british thermal unit

**Voltage In Volts:**

115.0

**Phase:**

Single

**Special Features:**

Metal is hot phosphoric acid treated and given 2 coats of primer before painted

**Frequency In Hertz:**

60.0

**Height:**

24.750 inches

**Quantity:**

1

**Unpackaged Unit Weight:**

191.00 pounds

**Surface Treatment:**

Enamel

**Surface Treatment Specification:**

Mil-e-15024, class 2 military specification single treatment response

**Specification Data:**

81349-mil-u-17293d government specification

**Specification Or Standard:**

1 type and 14 size

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A01300

**Mil-std (military Standard):**

Mil-e-15024 spec.