

View Online at <https://aerobasegroup.com/nsn/4520-01-274-4708>

Mounting Type:

Ceiling suspended

Heat Medium Type:

Hot water or steam

Maximum Pressure Limit:

25.0 pounds per square inch gage

Heat Outlet Quantity:

1

Heat Delivery Direction:

Horizontal

Heat Discharge Outlet Type:

Adjustable

Heat Directing Device:

Adjustable louver

Air Circulation Device:

Propeller fan

Speed Adjustments:

Single speed

Maximum Air Flow Rate:

500.0 cubic feet per minute

Circulated Air Type:

Heated

Width:

22.000 inches

Current Type:

Ac

Depth:

27.000 inches

Prime Mover Type:

Electric motor

Operating Control Type:

Any acceptable

Current Rating In Amps:

0.41

Heating Element Type:

Hot water coil or steam coil

Inclosure Material:

Steel

Heat Delivery Rate:

30000.0 british thermal unit

Voltage In Volts:

230.0

Phase:

Single

Special Features:

Hot phosphoric acid treatment before primer coats

Frequency In Hertz:

60.0

Height:

18.750 inches

Quantity:

1

Surface Treatment:

Primer

Surface Treatment Specification:

Tt-p-664 federal specification single treatment response

Specification Data:

81349-mil-u-17293d/sh/ government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A01300