NSN 4520-01-351-7938

Nonimmersion Type Electrical Heating Element - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4520-01-351-7938

| Mounting Method Style: | | | | | |
|---|--|--|--|--|--|
| Axial stud type mounting facility | | | | | |
| Body Style: | | | | | |
| Finned, tubular, u shaped | | | | | |
| Terminal Quantity: | | | | | |
| 2 | | | | | |
| Effective Heating Length: | | | | | |
| 8.750 inches | | | | | |
| Element Radiation Specificationtrum: | | | | | |
| Noninfrared | | | | | |
| Heat Control Type: | | | | | |
| Thermostat | | | | | |
| Element Connection Style: | | | | | |
| Hermetically sealed stud | | | | | |
| Heat Quantity: | | | | | |
| 1 | | | | | |
| Length: | | | | | |
| 8.750 inches | | | | | |
| End Application: | | | | | |
| Indeeco d200k0: b07246 item 01-24-2 stationary duct type heater | | | | | |
| Maximum Wattage Rating In Watts: | | | | | |
| 465.0 single voltage | | | | | |
| Element Quantity: | | | | | |
| 1 | | | | | |
| Thread Size: | | | | | |
| 0.190 inches mounting facility | | | | | |
| Thread Quantity: | | | | | |
| 32 per inch mounting facility | | | | | |
| Voltage In Volts And Current Type: | | | | | |
| 120.0 ac single voltage | | | | | |
| Phase: | | | | | |
| Single single voltage | | | | | |
| Special Features: | | | | | |
| Terminals are 2.500 in. Apart c to c | | | | | |
| Frequency In Hertz: | | | | | |
| 60.0 | | | | | |
| Material: | | | | | |
| Nickel alloy sheath | | | | | |
| Thread Series Designator: | | | | | |
| Unf mounting facility | | | | | |
| Shelf Life: | | | | | |

N/a

NSN 4520-01-351-7938

Nonimmersion Type Electrical Heating Element - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A01900