

View Online at <https://aerobasegroup.com/nsn/4520-01-470-3809>

Mounting Type:

Wall panel

Heat Medium Type:

Air

Outlet Position:

90 degrees apart

Heat Outlet Quantity:

2

Heat Delivery Direction:

Horizontal and vertical

Heat Discharge Outlet Type:

Stationary

Heat Directing Device:

Fixed louver

Width:

4.250 inches

Current Type:

Ac

Depth:

5.140 inches

Operating Control Type:

Thermostatic

Current Rating In Amps:

3.3

Heating Element Type:

Electric nonimmersion

Inclosure Material:

Aluminum

Heat Delivery Rate:

2729.6 british thermal unit

Voltage In Volts:

230.0

Phase:

Single

Special Features:

Adjustable thermostat 0.0 to plus 100.0 deg. F; terminal block has three 6-32 unc screw terminals, barriers are labeled for power and ground connections; ball bearing fan operates continuously; may be mounted on any flat sheet metal surface using four 10-32 unf self-tapping screws (included) through four 0.250 in. Dia. Holes, one located near each of the four corners of unit; do not install on wood panel; ul component recognized and csa listed

Frequency In Hertz:

50.0 or 60.0

Functional Description:

Heat and circulate air to protect sensitive mechanical, electrical, and electronic equipment from harmful effects of condensation, corrosion, and low temperatures

Height:

Surface Treatment:

Anodize

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A01300