

View Online at <https://aerobasegroup.com/nsn/4520-01-470-3809>

**Mounting Type:**

Wall panel

**Heat Medium Type:**

Air

**Outlet Position:**

90 degrees apart

**Heat Outlet Quantity:**

2

**Heat Delivery Direction:**

Horizontal and vertical

**Heat Discharge Outlet Type:**

Stationary

**Heat Directing Device:**

Fixed louver

**Width:**

4.250 inches

**Current Type:**

Ac

**Depth:**

5.140 inches

**Operating Control Type:**

Thermostatic

**Current Rating In Amps:**

3.3

**Heating Element Type:**

Electric nonimmersion

**Inclosure Material:**

Aluminum

**Heat Delivery Rate:**

2729.6 british thermal unit

**Voltage In Volts:**

230.0

**Phase:**

Single

**Special Features:**

Adjustable thermostat 0.0 to plus 100.0 deg. F; terminal block has three 6-32 unc screw terminals, barriers are labeled for power and ground connections; ball bearing fan operates continuously; may be mounted on any flat sheet metal surface using four 10-32 unf self-tapping screws (included) through four 0.250 in. Dia. Holes, one located near each of the four corners of unit; do not install on wood panel; ul component recognized and csa listed

**Frequency In Hertz:**

50.0 or 60.0

**Functional Description:**

Heat and circulate air to protect sensitive mechanical, electrical, and electronic equipment from harmful effects of condensation, corrosion, and low temperatures

**Height:**

**Surface Treatment:**

Anodize

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A01300