

View Online at <https://aerobasegroup.com/nsn/4520-01-558-8125>

Mounting Type:

Floor surface, free standing, nonducted

Heat Medium Type:

Air

Heat Outlet Quantity:

1

Heat Delivery Direction:

Horizontal

Heat Discharge Outlet Type:

Stationary

Heat Directing Device:

Flexible ducts

Air Circulation Device:

Blower wheel

Speed Adjustments:

Single speed

Maximum Air Flow Rate:

1500.0 cubic feet per minute

Circulated Air Type:

Heated

Width:

26.000 inches

Current Type:

Ac

End Application:

Bear water system, basic expeditionary air resources // force provider (cold weather kit)

Prime Mover Type:

Electric motor

Operating Control Type:

Automatic control switch

Current Rating In Amps:

12.0

Heating Element Type:

Burner

Ignition Method:

Electrode

Fuel Consumption Rate Per Hour:

1.3 gallons

Heat Delivery Rate:

120000.0 british thermal unit

Integral Fuel Tank Capacity:

22.0 gallons

Fuel Feed Method:

Internal pump

Product Name:

Heater assembly

Voltage In Volts:

110.0

Phase:

Single

Special Features:

Air filter type: no air filter // dimension: 56.000 in. length // color: green // accessories: remote thermostat and co detector x stack adapter x 16" by 10' flexible duct (qty.2) x power cord // available: insulated ducts // web site: www.Hdtglobal.Com

Frequency In Hertz:

60.0

Fuel Type:

Df-a arctic diesel fuel oil or df-1 winter diesel fuel oil or df-2 regular diesel fuel oil

Height:

31.000 inches

Quantity:

1

Supplementary Features:

Also use jp-8 military fuel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A01300