

View Online at <https://aerobasegroup.com/nsn/4610-01-093-2380>

Current Type:

Ac

Filtering Material:

Gravel and black coal and clear plastic and white aluminum silicate sand

Filter Quantity:

1

Prime Mover Horsepower Rating:

10.000

Motor Environmental Protection:

Mildew resistant

Prime Mover Type:

Electric motor

Filter Type:

Gravity

Potable Water Capacity:

600.0 gallons per hour

Disinfection Unit Type:

Chlorinator

Disinfection Unit Quantity:

1

Feed Type:

Solution

Feed Control Type:

Manual

Maximum Feed Rate:

12.0 liters per hour

Chemical Pot:

Provided

Pretreatment Equipment Type:

Chemical feeder

Chemical Feeder Type And Quantity:

4 solution

Filter Effectiveness In Square Feet:

4.9

Electromagnetic Interference Suppression:

Not provided

Voltage In Volts:

460.0

Phase:

Three

Special Features:

Four pressure tubes with two each reverse osmosis pressure-type filters in each tube; filters are sprial wound, manufactured from polyamide filtering material, rated at 3.0 square feet of filtering effectiveness; each filter cartridge uses a polypropylene tube which has an effective filtering area of 2.3 square feet

Frequency In Hertz:

60.0

Quantity:

4

Specification Or Standard:

1 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T227-c