

View Online at <https://aerobasegroup.com/nsn/4610-01-195-6297>

**Current Type:**

Ac

**Filtering Material:**

Gravel and black coal and clear plastic and white aluminum silicate sand

**Filter Quantity:**

1

**Prime Mover Horsepower Rating:**

10.000

**Motor Environmental Protection:**

Mildew resistant

**Prime Mover Type:**

Electric motor

**Filter Type:**

Gravity

**Potable Water Capacity:**

600.0 gallons per hour

**Disinfection Unit Type:**

Chlorinator

**Disinfection Unit Quantity:**

1

**Feed Type:**

Solution

**Feed Control Type:**

Manual

**Maximum Feed Rate:**

12.0 liters per hour

**Chemical Pot:**

Provided

**Pretreatment Equipment Type:**

Chemical feeder

**Chemical Feeder Type And Quantity:**

4 solution

**Filter Effectiveness In Square Feet:**

4.9

**Electromagnetic Interference Suppression:**

Not provided

**Voltage In Volts:**

460.0

**Phase:**

Three

**Special Features:**

Four pressure tubes with two each reverse osmosis pressure-type filters in each tube; filters are sprial wound, manufactured from polyamide filtering material, rated at 3.0 square feet of filtering effectiveness; each filter cartridge uses a polypropylene tube which has an effective filtering area of 2.3 square feet

**Frequency In Hertz:**

60.0

**Quantity:**

4

**Furnished Items And Quantity:**

1 chemical pot

**Specification Or Standard:**

Pe 3 type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T227-c