

View Online at <https://aerobasegroup.com/nsn/4710-00-073-2184>

Wall Thickness:

0.035 inches

Thread Class:

3b second end

Thread Direction:

Right-hand second end

Mating End Quantity:

1 second end

Tubing Material:

Aluminum alloy, mil-t-7081, comp 6061, temper t6

End Connection Style:

Swivel nut with loose or integral clinch sleeve second end

Seat Angle In Deg:

33.0 first end

Design Form:

Prebent

Tube Outside Diameter:

0.250 inches

End Connection Specification/std:

Mil, an818, part no. An818-4d, mil, ms20819, part no. Ms20819-4d, andmil, 21921, part no. Ms21921-4d, mil, ms21922, part no. Ms21922-4

Thread Size:

0.438 inches single end

Material:

Aluminum alloy, qq-a-225/4, temper t6 and aluminum alloy, qq-a-225/6 temper t6 or t851, aluminumalloy, qq-a-225/6, temper t6 or t851, and steel, qq-s-637 single end

Material:

Aluminum alloy, qq-a-225/4, temper t6 and aluminum alloy, qq-a-225/6 temper t6 or t851, aluminumalloy, qq-a-225/6, temper t6 or t851, and steel, qq-s-637 single end

Thread Series Designator:

Unf single end

Fsc Application Data:

Fuselage sect., acft

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T383-d