## NSN 4710-00-590-2432

Metallic Tube - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4710-00-590-2432

| Cross Sectional Shape:  |
|---|
| Plain round   |
| Wall Thickness:   |
| 0.035 inches  |
| First End Style:  |
| Plain   |
| Diameter:   |
| 0.375 inches  |
| Maximum Operating Temp:   |
| -800.0 degrees fahrenheit                                       |
| Second End Relationship With First End:                         |
| Identical   |
| Construction:   |
| Seamless  |
| Maximum Operating Pressure:                                     |
| 3800.0 pounds per square inch                                   |
| Measuring Method And Length:                                    |
| 204.000 inches random and 288.000 inches random                 |
| Special Features:   |
| Tube ends sealed w/plastic caps to exclude dirt                 |
| Heat Treatment:   |
| Annealed and cold drawn   |
| Material:   |
| Steel comp 304  |
| Material Specification:   |
| Mil-t-8504 military specification single material response      |
| Surface Treatment:  |
| Passivate outside   |
| Specification Data:   |
| 81343-ams5567 professional/industrial association specification |
| Specification Or Standard:                                      |
| A condition and 304 type  |
| Departure From Cited Document:                                  |
| As modified by tube Ig  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| Demilitarization:   |
| No  |
| Fiig:   |

A004a0

## NSN 4710-00-590-2432

Metallic Tube - Page 2 of 2



Mil-std (military Standard):

Mil-t-8504 spec.