## NSN 4710-00-684-1424

Metallic Tube - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4710-00-684-1424

Cross Sectional Shape:  Plain round  Wall Thickness: 0.016 inches  First End Style:  Plain  Diameter: 0.125 inches  Maximum Operating Temp: -800.0 degrees fahrenheit  Second End Relationship With First End: Identical  Construction: Seamless  Maximum Operating Pressure: 3000.0 pounds per square inch  Measuring Method And Length: 120.000 inches random and 192.000 inches random  Heat Treatment:  Annealed  Material: Steel  Material Specification: Mil-t-8504 military specification single material response  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Specification Data:
Wall Thickness: 0.016 inches First End Style: Plain Diameter: 0.125 inches Maximum Operating Temp: -800.0 degrees fahrenheit Second End Relationship With First End: Identical Construction: Seamless Maximum Operating Pressure: 3000.0 pounds per square inch Measuring Method And Length: 120.000 inches random and 192.000 inches random Heat Treatment: Annealed Material: Steel Material Specification: Mil-t-8504 military specification single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
O.016 inches  First End Style: Plain  Diameter: 0.125 inches  Maximum Operating Temp: -800.0 degrees fahrenheit  Second End Relationship With First End: Identical  Construction: Seamless  Maximum Operating Pressure: 3000.0 pounds per square inch  Measuring Method And Length: 120.000 inches random and 192.000 inches random  Heat Treatment: Annealed  Material: Steel  Material Specification: Mil-t-8504 military specification single material response  Surface Treatment: Passivate  Surface Treatment Specification: Qq-p-35 federal specification single treatment response
First End Style: Plain  Diameter: 0.125 inches  Maximum Operating Temp: -800.0 degrees fahrenheit  Second End Relationship With First End: Identical  Construction: Seamless  Maximum Operating Pressure: 3000.0 pounds per square inch  Measuring Method And Length: 120.000 inches random and 192.000 inches random  Heat Treatment:  Annealed  Material: Steel  Material Specification: Mil-t-8504 military specification single material response  Surface Treatment: Passivate  Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Plain  Diameter:  0.125 inches  Maximum Operating Temp: -800.0 degrees fahrenheit  Second End Relationship With First End: Identical  Construction: Seamless  Maximum Operating Pressure: 3000.0 pounds per square inch  Measuring Method And Length: 120.000 inches random and 192.000 inches random  Heat Treatment: Annealed  Material: Steel  Material Specification: Mil-t-8504 military specification single material response  Surface Treatment: Passivate  Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Diameter:  0.125 inches  Maximum Operating Temp: -800.0 degrees fahrenheit  Second End Relationship With First End: Identical  Construction: Seamless  Maximum Operating Pressure: 3000.0 pounds per square inch  Measuring Method And Length: 120.000 inches random and 192.000 inches random  Heat Treatment: Annealed  Material: Steel  Material Specification: Mil-t-8504 military specification single material response  Surface Treatment: Passivate  Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Maximum Operating Temp: -800.0 degrees fahrenheit Second End Relationship With First End: Identical Construction: Seamless Maximum Operating Pressure: 3000.0 pounds per square inch Measuring Method And Length: 120.000 inches random and 192.000 inches random Heat Treatment: Annealed Material: Steel Material Specification: Mil-t-8504 military specification single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Maximum Operating Temp: -800.0 degrees fahrenheit Second End Relationship With First End: Identical Construction: Seamless Maximum Operating Pressure: 3000.0 pounds per square inch Measuring Method And Length: 120.000 inches random and 192.000 inches random Heat Treatment: Annealed Material: Steel Material Specification: Mil-t-8504 military specification single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
-800.0 degrees fahrenheit  Second End Relationship With First End: Identical  Construction: Seamless  Maximum Operating Pressure: 3000.0 pounds per square inch  Measuring Method And Length: 120.000 inches random and 192.000 inches random  Heat Treatment: Annealed  Material: Steel  Material Specification: Mil-t-8504 military specification single material response  Surface Treatment: Passivate  Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Second End Relationship With First End: Identical Construction: Seamless Maximum Operating Pressure: 3000.0 pounds per square inch Measuring Method And Length: 120.000 inches random and 192.000 inches random Heat Treatment: Annealed Material: Steel Material Specification: Mil-t-8504 military specification single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Construction: Seamless Maximum Operating Pressure: 3000.0 pounds per square inch Measuring Method And Length: 120.000 inches random and 192.000 inches random Heat Treatment: Annealed Material: Steel Material Specification: Mil-t-8504 military specification single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Construction: Seamless Maximum Operating Pressure: 3000.0 pounds per square inch Measuring Method And Length: 120.000 inches random and 192.000 inches random Heat Treatment: Annealed Material: Steel Material Specification: Mil-t-8504 military specification single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Seamless  Maximum Operating Pressure: 3000.0 pounds per square inch  Measuring Method And Length: 120.000 inches random and 192.000 inches random  Heat Treatment: Annealed  Material: Steel  Material Specification: Mil-t-8504 military specification single material response  Surface Treatment: Passivate  Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Maximum Operating Pressure: 3000.0 pounds per square inch  Measuring Method And Length: 120.000 inches random and 192.000 inches random  Heat Treatment: Annealed  Material: Steel  Material Specification: Mil-t-8504 military specification single material response  Surface Treatment: Passivate  Surface Treatment Specification: Qq-p-35 federal specification single treatment response
3000.0 pounds per square inch  Measuring Method And Length: 120.000 inches random and 192.000 inches random  Heat Treatment: Annealed  Material: Steel  Material Specification: Mil-t-8504 military specification single material response  Surface Treatment: Passivate  Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Measuring Method And Length:  120.000 inches random and 192.000 inches random  Heat Treatment:  Annealed  Material:  Steel  Material Specification:  Mil-t-8504 military specification single material response  Surface Treatment:  Passivate  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response
120.000 inches random and 192.000 inches random  Heat Treatment:  Annealed  Material: Steel  Material Specification:  Mil-t-8504 military specification single material response  Surface Treatment:  Passivate  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response
Heat Treatment:  Annealed  Material: Steel  Material Specification: Mil-t-8504 military specification single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Annealed  Material: Steel  Material Specification: Mil-t-8504 military specification single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Material: Steel  Material Specification: Mil-t-8504 military specification single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Steel  Material Specification:  Mil-t-8504 military specification single material response  Surface Treatment:  Passivate  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response
Material Specification:  Mil-t-8504 military specification single material response  Surface Treatment:  Passivate  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response
Mil-t-8504 military specification single material response  Surface Treatment:  Passivate  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response
Surface Treatment:  Passivate  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response
Passivate  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response
Surface Treatment Specification:  Qq-p-35 federal specification single treatment response
Qq-p-35 federal specification single treatment response
Specification Data:
81349-mil-t-8504 government specification
Specification Or Standard:
1 type
Shelf Life:
N/a
Unit Of Measure:
Ont of modouro.
Demilitarization:
Demilitarization:
Demilitarization:

Mil-t-8504 spec.