NSN 4710-00-926-1180

Metallic Tube - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4710-00-926-1180

Plain round Wall Thickness: 0.072 inches First End Style: Plain Diameter: Between 0.535 inches and 0.540 inches Second End Relationship With First End: Identical Construction: Seamless Maximum Operating Pressure: 3300.0 pounds per square inch Criticality Code Justification: Zzzx Measuring Method And Length: 144.000 inches random and 240.000 inches random Heat Treatment: Annealed Material:
O.072 inches First End Style: Plain Diameter: Between 0.535 inches and 0.540 inches Second End Relationship With First End: Identical Construction: Seamless Maximum Operating Pressure: 3300.0 pounds per square inch Criticality Code Justification: Zzzx Measuring Method And Length: 144.000 inches random and 240.000 inches random Heat Treatment: Annealed
First End Style: Plain Diameter: Between 0.535 inches and 0.540 inches Second End Relationship With First End: Identical Construction: Seamless Maximum Operating Pressure: 3300.0 pounds per square inch Criticality Code Justification: Zzzx Measuring Method And Length: 144.000 inches random and 240.000 inches random Heat Treatment: Annealed
Plain Diameter: Between 0.535 inches and 0.540 inches Second End Relationship With First End: Identical Construction: Seamless Maximum Operating Pressure: 3300.0 pounds per square inch Criticality Code Justification: Zzzx Measuring Method And Length: 144.000 inches random and 240.000 inches random Heat Treatment: Annealed
Diameter: Between 0.535 inches and 0.540 inches Second End Relationship With First End: Identical Construction: Seamless Maximum Operating Pressure: 3300.0 pounds per square inch Criticality Code Justification: Zzzx Measuring Method And Length: 144.000 inches random and 240.000 inches random Heat Treatment: Annealed
Between 0.535 inches and 0.540 inches Second End Relationship With First End: Identical Construction: Seamless Maximum Operating Pressure: 3300.0 pounds per square inch Criticality Code Justification: Zzzx Measuring Method And Length: 144.000 inches random and 240.000 inches random Heat Treatment: Annealed
Second End Relationship With First End: Identical Construction: Seamless Maximum Operating Pressure: 3300.0 pounds per square inch Criticality Code Justification: Zzzx Measuring Method And Length: 144.000 inches random and 240.000 inches random Heat Treatment: Annealed
Identical Construction: Seamless Maximum Operating Pressure: 3300.0 pounds per square inch Criticality Code Justification: Zzzx Measuring Method And Length: 144.000 inches random and 240.000 inches random Heat Treatment: Annealed
Construction: Seamless Maximum Operating Pressure: 3300.0 pounds per square inch Criticality Code Justification: Zzzx Measuring Method And Length: 144.000 inches random and 240.000 inches random Heat Treatment: Annealed
Seamless Maximum Operating Pressure: 3300.0 pounds per square inch Criticality Code Justification: Zzzx Measuring Method And Length: 144.000 inches random and 240.000 inches random Heat Treatment: Annealed
Maximum Operating Pressure: 3300.0 pounds per square inch Criticality Code Justification: Zzzx Measuring Method And Length: 144.000 inches random and 240.000 inches random Heat Treatment: Annealed
3300.0 pounds per square inch Criticality Code Justification: Zzzx Measuring Method And Length: 144.000 inches random and 240.000 inches random Heat Treatment: Annealed
Criticality Code Justification: Zzzx Measuring Method And Length: 144.000 inches random and 240.000 inches random Heat Treatment: Annealed
Measuring Method And Length: 144.000 inches random and 240.000 inches random Heat Treatment: Annealed
Measuring Method And Length: 144.000 inches random and 240.000 inches random Heat Treatment: Annealed
144.000 inches random and 240.000 inches random Heat Treatment: Annealed
Heat Treatment: Annealed
Annealed
Material:
Copper alloy
Material Specification:
Astm b111-62, alloy 70-30 assn standard single material response
Specification Or Standard:
I type and ii grade and 3300 class and 70-30 composition
Departure From Cited Designator:
Quality control iaw navships 0948-045-7010 material identification and control instruction for level 1 items
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A004a0