

View Online at <https://aerobasegroup.com/nsn/4710-01-384-0825>

Wall Thickness:

0.039 inches

Thread Class:

3a second end

Thread Direction:

Right-hand second end

Mating End Quantity:

1 second end

Tubing Material:

Brass, qq-b-626, 1/2 hard

End Connection Style:

Flared second end

Seat Angle In Deg:

37.0 second end

Design Form:

Prebent

Connection Specificational Design:

Union second end

Tube Outside Diameter:

0.375 inches

End Connection Specification/std:

Mil, ms33656, part no. Ms33656g-6

Thread Size:

0.562 inches second end

Material:

Brass, qq-b-626, 1/2 hard second end

Material:

Copper alloy 268 or copper alloy 260 or copper alloy 240 or copper alloy 230 or copper alloy 377 or copper alloy 360 or copper alloy 342 or copper alloy 353 or copper alloy 262 or copper alloy 270 or copper alloy 272 or copper alloy 274 or copper alloy 280 or copper alloy 330 or copper alloy 331 or copper alloy 332 or copper alloy 335 or copper alloy 340 or copper alloy 342 or copper alloy 344 or copper alloy 345 or copper alloy 347 or copper alloy 348 or copper alloy 350 or copper alloy 356 or copper alloy 370 or copper alloy 462 or copper alloy 464 or copper alloy 465 or copper alloy 466 or copper alloy 467 or copper alloy 482 or copper alloy 485 second end

Thread Series Designator:

Unjf second end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T383-d