

View Online at <https://aerobasegroup.com/nsn/4710-01-465-9038>

Wall Thickness:

0.028 inches

Thread Class:

2b second end

Thread Direction:

Right-hand second end

Overall Length:

1050.2 millimeters

Mating End Quantity:

1 second end

End Application:

Light armored vehicle, air defense

Tubing Material:

Steel, aisi 304

End Connection Style:

Swivel nut, flared second end

Seat Angle In Deg:

45.0 first end

Design Form:

Prebent

Tube Outside Diameter:

0.250 inches

Thread Size:

0.438 inches second end

Special Features:

250 inch o.D. Tube assembly with on 45 degree double flared end, one 37 degree single flared end; connectors - 45 degree end has flared nut (sae j5124010110) - 37 degree end has swivel nut (ms51531-b4) and compression sleeve (ms51533-b4); tube has six bends

Material:

Brass, qq-b-626, 1/2 hard second end and steel, corrosion resisting second end

Material:

Copper alloy 268 or copper alloy 260 or copper alloy 240 or copper alloy 230 or copper alloy 377 or copper alloy 360 or copper alloy 342 or copper alloy 353 or copper alloy 262 or copper alloy 270 or copper alloy 272 or copper alloy 274 or copper alloy 280 or copper alloy 330 or copper alloy 331 or copper alloy 332 or copper alloy 335 or copper alloy 340 or copper alloy 342 or copper alloy 344 or copper alloy 345 or copper alloy 347 or copper alloy 348 or copper alloy 350 or copper alloy 356 or copper alloy 370 or copper alloy 462 or copper alloy 464 or copper alloy 465 or copper alloy 466 or copper alloy 467 or copper alloy 482 or copper alloy 485 and stainless steel second end

Thread Series Designator:

Unf second end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig: