NSN 4720-00-001-3456

Cross Sectional Shape:

Unf 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-001-3456

Round					
Thread Class:					
2b 1st end					
Thread Direction:					
Right-hand 1st end					
Inside Diameter:					
0.375 inches					
Tempurature Rating:					
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response					
Outside Diameter:					
0.812 inches					
Minimum Inside Bending Radius:					
5.000 inches					
Connection Style:					
Swivel nut flare 1st end					
End Connection Design:					
Straight 1st end					
Connection Type:					
Threaded internal tube 1st end					
Burst Test Pressure:					
9000.0 pounds per square inch					
Layer Composition And Location:					
1st layer braided wire and outer layer molded rubber, synthetic					
Maximum Operating Pressure:					
2250.0 pounds per square inch					
Thread Size:					
0.750 inches 1st end					
Seat Angle:					
37.0 degrees 1st end					
Hydrostatic Test Pressure:					
4500.0 pounds per square inch					
Outer Covering Environmental Protection:					
Oil resistant and weatherproof					
Inside Surface Condition:					
Smooth					
Measuring Method And Length:					
54.000 inches					
Media For Which Designed:					
Fuel/oil, hydrocarbon single response					
Thread Series Designator:					

NSN 4720-00-001-3456

Nonmetallic Hose Assembly - Page 2 of 2



_				
c	hο	JIF.		ife:
J	116		_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0