Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-001-3491

| Cross Sectional Shape: |
|---|
| Round |
| Thread Class: |
| 2b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.250 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.500 inches |
| Minimum Inside Bending Radius: |
| 2.500 inches |
| Exterior Color: |
| Black |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Straight 2nd end |
| Connection Type: |
| Threaded internal tube 1st end |
| Burst Test Pressure: |
| 1000.0 pounds per square inch |
| Layer Composition And Location: |
| Outer layer molded rubber, chloroprene and 1st layer braided rayon cord |
| Maximum Operating Pressure: |
| 250.0 pounds per square inch |
| Thread Size: |
| 0.500 inches 2nd end |
| Seat Angle: |
| 45.0 degrees 1st end |
| Hydrostatic Test Pressure: |
| 500.0 pounds per square inch |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 22.000 inches |
| Media For Which Designed: |
| Fuel/oil, hydrocarbon single response |
| Thread Series Designator: |
| Unf 2nd end |

NSN 4720-00-001-3491

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

