NSN 4720-00-001-6339

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-001-6339

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.500 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.968 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
16 1st end
Burst Test Pressure:
14000.0 pounds per square inch
Layer Composition And Location:
2nd layer braided steel wire and outer layer molded rubber, synthetic and 1st layer braided steel wire
Maximum Operating Pressure:
3500.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
7000.0 pounds per square inch
Outer Covering Environmental Protection:
Mildew resistant and oil resistant and oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
21.500 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:

Unf 1st end

NSN 4720-00-001-6339

Nonmetallic Hose Assembly - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0