NSN 4720-00-001-9553

Cross Sectional Shape:

Round

Thread Class:

5.750 inches working

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-001-9553

3b 1st end				
Thread Direction:				
Right-hand 1st end				
Inside Diameter:				
0.229 inches				
Tempurature Rating:				
-54.0 degrees celsius single response and 204.0 degrees celsius single response				
Outside Diameter:				
0.420 inches				
Minimum Inside Bending Radius:				
3.000 inches				
Connection Style:				
Swivel nut flare 2nd end				
End Connection Design:				
Straight 1st end				
Connection Type:				
Threaded internal tube 1st end				
Features Provided:				
Electrostatic discharge capability				
Burst Test Pressure:				
16000.0 pounds per square inch				
Layer Composition And Location:				
Outer layer braided corrosion resistant steel wire				
Maximum Operating Pressure:				
3000.0 pounds per square inch				
Thread Size:				
0.438 inches 1st end				
Seat Angle:				
37.0 degrees 2nd end				
Hydrostatic Test Pressure:				
6000.0 pounds per square inch				
Flow Angle:				
45.0 degrees 2nd end				
Outer Covering Environmental Protection:				
Abrasion resistant				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				

NSN 4720-00-001-9553

Nonmetallic Hose Assembly - Page 2 of 2



		•		
Ιh	read	Series	Desiar	າator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0