NSN 4720-00-003-3612

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:

Tempurature Rating:

Between 0.750 inches and 0.780 inches

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-003-3612

-65.0 degrees fahrenheit single response and 350.0 degrees fahrenheit single response
Outside Diameter:
1.090 inches
Minimum Inside Bending Radius:
2.000 inches
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
700.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
175.0 pounds per square inch
Thread Size:
1.062 inches 1st end
Seat Angle:
12.0 degrees 1st end
Hydrostatic Test Pressure:
350.0 pounds per square inch
Outer Covering Environmental Protection:
Corrosion resistant
Inside Surface Condition:
Convoluted
Measuring Method And Length:
15.625 inches working

NSN 4720-00-003-3612

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:
Un 1st end
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0