Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-003-5383

| Cross Sectional Shape: | |
|--|----------------------|
| Round | |
| Thread Class: | |
| 3b 1st end | |
| | |
| Thread Direction: | |
| Right-hand 1st end | |
| Inside Diameter: | |
| Between 0.500 inches and 0.530 inches | |
| Tempurature Rating: | ·· · · |
| -65.0 degrees fahrenheit single response and 350.0 degrees fahrenh | neit single response |
| Outside Diameter: | |
| 0.780 inches | |
| Minimum Inside Bending Radius: | |
| 1.000 inches | |
| Connection Style: | |
| Swivel nut, flareless 1st end | |
| End Connection Design: | |
| Straight 1st end | |
| Connection Type: | |
| Threaded internal tube 1st end | |
| Features Provided: | |
| Electrostatic discharge capability | |
| Burst Test Pressure: | |
| 800.0 pounds per square inch | |
| Layer Composition And Location: | |
| Outer layer braided corrosion resistant steel wire | |
| Maximum Operating Pressure: | |
| 200.0 pounds per square inch | |
| Thread Size: | |
| 0.750 inches 1st end | |
| Seat Angle: | |
| 12.0 degrees 1st end | |
| Hydrostatic Test Pressure: | |
| 400.0 pounds per square inch | |
| Outer Covering Environmental Protection: | |
| Corrosion resistant | |
| Inside Surface Condition: | |
| Convoluted | |
| Measuring Method And Length: | |
| 17.000 inches working | |
| Thread Series Designator: | |
| Unjf 1st end | |
| | |

NSN 4720-00-003-5383

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

