NSN 4720-00-003-5388

N/a

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-003-5388

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.212 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diameter:
0.507 inches
Minimum Inside Bending Radius:
3.000 inches
Connection Style:
Swivel nut, inverted flare 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
24 2nd end
Burst Test Pressure:
16000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
8.5 degrees 2nd end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
13.750 inches working
Thread Series Designator:
Unjs 2nd end
Shelf Life:

NSN 4720-00-003-5388

Nonmetallic Hose Assembly - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A542a0