

View Online at <https://aerobasegroup.com/nsn/4720-00-004-1158>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.602 inches

Temperature Rating:

-65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response

Outside Diameter:

1.140 inches

Minimum Inside Bending Radius:

7.750 inches

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting stainless steel all ends

Fitting Component And Surface Treatment:

Complete fitting passivate 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Electrostatic discharge capability

Thready Qty Per Inch (tpi):

12 1st end

Second End Relationship With First End:

Identical

Burst Test Pressure:

12000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

1.062 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Outer Covering Environmental Protection:

Corrosion resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

17.125 inches working and 17.375 inches working

Special Features:

Inner conveying tube material-plastic, polytetrafluoroethylene

Media For Which Designed:

Air and hydraulic fluid single response

Thread Series Designator:

Unj 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0