## NSN 4720-00-004-8231

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-004-8231

| Cross Sectional Shape  |
|--|
| Cross Sectional Shape:   |
| Round Thread Directions  |
| Thread Direction:  |
| Right-hand 1st end   |
| Inside Diameter:   |
| 0.375 inches   |
| Tempurature Rating:  |
| -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response  |
| Outside Diameter:  |
| 0.625 inches   |
| Minimum Inside Bending Radius:   |
| 1.250 inches   |
| Connection Style:  |
| Inverted flare 1st end   |
| End Connection Design:   |
| Straight 1st end   |
| Connection Type:   |
| Threaded external pipe 1st end   |
| Burst Test Pressure:   |
| 9000.0 pounds per square inch  |
| Layer Composition And Location:  |
| 2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord and 1st layer braided textile yarn |
| Maximum Operating Pressure:  |
| 2250.0 pounds per square inch  |
| Thread Size:   |
| 0.375 inches 1st end   |
| Seat Angle:  |
| 30.0 degrees 1st end   |
| Outer Covering Environmental Protection:   |
| Cold resistant and fire resistant and mildew resistant and oil resistant   |
| Inside Surface Condition:  |
| Smooth   |
| Measuring Method And Length:   |
| 62.500 inches  |
| Media For Which Designed:  |
| Fuel/oil, hydrocarbon single response  |
| Thread Series Designator:  |
| Nptf 1st end   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |

-

## NSN 4720-00-004-8231

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0