Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-004-8425

Cross Sect	tional Shape:
Round	
Thread Cla	ss:
3b 1st end	
Thread Dir	ection:
Right-hand	1st end
Inside Diar	neter:
0.625 inche	s
Tempuratu	re Rating:
-65.0 degre	es fahrenheit and 180.0 degrees fahrenheit single response
Outside Di	ameter:
0.906 inche	S
Connectio	n Style:
Swivel nut f	lare 1st end
End Conne	ection Design:
Straight 1st	end
Connectio	n Type:
Threaded ir	nternal tube 1st end
Thready Q	ty Per Inch (tpi):
14 1st end	
Burst Test	Pressure:
700.0 poun	ds per square inch
Layer Com	position And Location:
Outer layer	molded rubber, synthetic and 1st layer braided cotton cord
Maximum	Operating Pressure:
125.0 poun	ds per square inch
Thread Siz	e:
0.875 inche	s 1st end
Seat Angle	: :
37.0 degree	es 1st end
Hydrostati	c Test Pressure:
250.0 poun	ds per square inch
Outer Cove	ering Environmental Protection:
Abrasion re	sistant and fuel resistant and oil resistant and water resistant and cold resistant and alcohol resistant
Inside Surf	ace Condition:
Smooth	
Measuring	Method And Length:
180.000 inc	hes
Media For	Which Designed:
Air single re	-
-	ies Designator:
Unjf 1st end	

## NSN 4720-00-004-8425

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0

