Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-00-004-9550

Cros	ss Sectional Shape:
Rour	nd
Insic	de Diameter:
0.25	0 inches
Tem	purature Rating:
-40.0) degrees fahrenheit and 200.0 degrees fahrenheit single response
Outs	side Diameter:
0.50	0 inches
Mini	mum Inside Bending Radius:
4.00	0 inches
Quic	k Disconnect Size:
0.25	0 inches 2nd end
Con	nection Style:
Push	n (internal) 1st end
End	Connection Design:
Strai	ght 2nd end
Con	nection Type:
Inter	nal quick disconnect 1st end
Burs	st Test Pressure:
2000	00.0 pounds per square inch
Laye	er Composition And Location:
Oute	r layer molded plastic and 1st layer braided synthetic cord
Maxi	imum Operating Pressure:
5000	0.0 pounds per square inch
Oute	er Covering Environmental Protection:
Hydr	aulic solution resistant and weatherproof
Insic	le Surface Condition:
Smo	oth
Mea	suring Method And Length:
74.5	00 inches
Shel	f Life:
N/a	
Unit	Of Measure:
Dem	ilitarization:
No	
Fiig:	
	2a0