## NSN 4720-00-005-1132

**Cross Sectional Shape:** 

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-005-1132

Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.620 inches
Minimum Inside Bending Radius:
3.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
1200.0 pounds per square inch
Layer Composition And Location:
Outer layer braided cotton cord and 1st layer braided fiber
Maximum Operating Pressure:
300.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
37.0 degrees 1st end
Outer Covering Environmental Protection:
Mildew resistant and oil resistant
Vacuum In Torr:
50.8
Inside Surface Condition:
Smooth
Measuring Method And Length:
24.000 inches
Media For Which Designed:
Air and ethylene glycol and fuel/oil, hydrocarbon and water single response
Thread Series Designator:
Unf 1st end

## NSN 4720-00-005-1132

Nonmetallic Hose Assembly - Page 2 of 2



She	lf	I if	ρ.
~	•••		•

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0