## NSN 4720-00-005-3538

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-005-3538

Cross Sectional Shape:
Round
Inside Diameter:
0.625 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 275.0 degrees fahrenheit single response
Outside Diameter:
1.078 inches
Minimum Inside Bending Radius:
6.500 inches
Exterior Color:
Black
Quick Disconnect Size:
1.062 inches 1st end
Connection Style:
Push (external) 1st end
End Connection Design:
Straight 1st end
Connection Type:
External quick disconnect 1st end
Burst Test Pressure:
6000.0 pounds per square inch
Layer Composition And Location:
2nd layer braided corrosion resistant steel wire and outer layer rubber impregnated braided fabric and 1st layer braided textile yarn
Maximum Operating Pressure:
1500.0 pounds per square inch
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Outer Covering Environmental Protection:
Cold resistant and corrosion resistant and mildew resistant and oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
180.000 inches
Special Features:
Furnished with aluminum caps and chains
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Shelf Life:
N/a
Unit Of Measure:

## NSN 4720-00-005-3538

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0