

View Online at <https://aerobasegroup.com/nsn/4720-00-006-3552>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.438 inches

**Temperature Rating:**

-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response

**Flange Thickness:**

0.800 inches 2nd end

**Outside Diameter:**

0.625 inches

**Minimum Inside Bending Radius:**

1.750 inches

**Exterior Color:**

Green

**Connection Style:**

Swivel nut with compression sleeve 1st end

**Bolt Hole Diameter:**

0.650 inches 2nd end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Unthreaded fluid passage bolt 2nd end

**Features Provided:**

Nuts drilled for lockwire

**Burst Test Pressure:**

600.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided synthetic cord

**Maximum Operating Pressure:**

150.0 pounds per square inch

**Thread Size:**

0.625 inches 1st end

**Seat Angle:**

12.0 degrees 1st end

**Hydrostatic Test Pressure:**

300.0 pounds per square inch

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

12.500 inches

**Media For Which Designed:**

Air single response

**Thread Series Designator:**

Unf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0