## NSN 4720-00-006-6080

**Cross Sectional Shape:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-006-6080

Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response
Outside Diameter:
0.590 inches
Minimum Inside Bending Radius:
4.000 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Nonskive and reusable end fittings
Burst Test Pressure:
23200.0 pounds per square inch
Layer Composition And Location:
2nd layer braided wire and outer layer molded rubber, synthetic and 1st layer braided wire
Maximum Operating Pressure:
5800.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Outer Covering Environmental Protection:
Abrasion resistant and oil resistant and weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
54.750 inches
Media For Which Designed:

Fuel/oil, hydrocarbon and hydraulic fluid, water base single response

## NSN 4720-00-006-6080

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Designator:
	_	

Unf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0