Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-006-6158

# **Cross Sectional Shape:** Round **Inside Diameter:** 0.500 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Flange Thickness: 0.270 inches 2nd end **Outside Diameter:** 0.922 inches **Minimum Inside Bending Radius:** 7.000 inches **Exterior Color:** Black Angle Between Rigid Elbow Fittings In Deg: 90.0 Flange Outside Diameter: 1.500 inches 1st end **Connection Style:** Plain w/ gasket groove (sae flanged head) 2nd end **End Flange Construction:** Solid 2nd end **End Connection Design:** Elbow 2nd end **Connection Type:** Plain face flange 2nd end **Burst Test Pressure:** 8000.0 pounds per square inch Layer Composition And Location:

2nd layer braided cotton cord and outer layer spirally wrapped rubber fabric and 1st layer braided steel wire

## **Maximum Operating Pressure:**

2000.0 pounds per square inch

## Flow Angle:

67.5 degrees 2nd end

#### **Outer Covering Environmental Protection:**

Cold resistant and oil resistant

# Inside Surface Condition:

Smooth

#### **Measuring Method And Length:**

37.000 inches working

### Flange Style:

Round w/ out bolt holes 2nd end

Nonmetallic Hose Assembly - Page 2 of 2



Media For Which Designed:

Fuel/oil, hydrocarbon single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0