NSN 4720-00-007-4604

Inner conveying tube material-rubber, synthetic

Media For Which Designed:

Water single response

Cross Sectional Shape:

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-007-4604

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.750 inches
Exterior Color:
Black
Hose Or Tubing Specification/std Data:
Zz-h-601, grade 3, class 1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in
specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on
certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Connection Style:
Swivel nut, gasket seal 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting copper alloy all ends
Connection Type:
Threaded internal hose 1st end
Thready Qty Per Inch (tpi):
11-1/2 1st end
Second End Relationship With First End:
Identical
Burst Test Pressure:
600.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
Outer layer molded rubber, synthetic
Maximum Operating Pressure:
150.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Outer Covering Environmental Protection:
Ozone resistant and weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
72.000 inches excluding end fittings
Special Features:

NSN 4720-00-007-4604

Fiig: A542a0

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:
Nh 1st end
Specification Data:
Zz-h-601, grade 3, class 1 professional/industrial association specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No