NSN 4720-00-007-4644

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-007-4644

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.687 inches
Minimum Inside Bending Radius:
4.000 inches
Exterior Color:
Black
Hose Or Tubing Specification/std Data:
Mil mil-h-13531, type 2 or 3, class a or b specification (includes engineering type bulletins, brochures, etc., that reflect specification type
data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data
on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting steel all ends
Fitting Component And Surface Treatment:
Complete fitting cadmium 1st end
Connection Type:
Threaded internal tube 1st end
Second End Relationship With First End:
Identical
Burst Test Pressure:
20000.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
Outer layer molded rubber
Maximum Operating Pressure:
5000.0 pounds per square inch

0.438 inches 1st end

Thread Size:

Unable To Decode:

Unable to decode or unable to decode

NSN 4720-00-007-4644Nonmetallic Hose Assembly - Page 2 of 2



Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
10000.0 pounds per square inch
Outer Covering Environmental Protection:
Mildew resistant and oil resistant and oil resistant
nside Surface Condition:
Smooth
Measuring Method And Length:
10.750 inches working
Special Features:
nner conveying tube material-rubber, synthetic
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Jnf 1st end
Specification Data:
Mil mil-h-13531, type 2 or 3, class a or b professional/industrial association specification and 96906-ms500083 government standard
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A542a0