

View Online at <https://aerobasegroup.com/nsn/4720-00-009-2413>

Cross Sectional Shape:

Round

Inside Diameter:

0.875 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 375.0 degrees fahrenheit single response

Outside Diameter:

1.156 inches

Minimum Inside Bending Radius:

5.500 inches

Angle Between Rigid Elbow Fittings In Deg:

52.0

Center To Center Distance Between Bolt Holes Along Width:

1.812 inches 1st end

Center To Center Distance Between Bolt Holes Along Length:

1.812 inches 1st end

Bolt Hole Quantity:

4 2nd end

Flange Length:

2.375 inches 1st end

Flange Width:

2.375 inches 1st end

Connection Style:

Plain swivel 2nd end

Bolt Hole Diameter:

0.266 inches 2nd end

End Flange Construction:

Split 2nd end

End Connection Design:

Elbow 2nd end

Connection Type:

Plain face flange 2nd end

Features Provided:

Electrostatic discharge capability

Burst Test Pressure:

2500.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

750.0 pounds per square inch

Hydrostatic Test Pressure:

1500.0 pounds per square inch

Flow Angle:

45.0 degrees 1st end

Outer Covering Environmental Protection:

Corrosion resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

21.625 inches working and 22.125 inches working

Flange Style:

Rectangular (includes square) 2nd end

Special Features:

Braided fire sleeve, non-asbestos

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Supplementary Features:

This item has been reviewed for asbestos material; the current approved sources; 00624 have indicated their part number contained asbestos prior to 1984; they continue to manufacture the same part number without asbestos material after 1984

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0