

View Online at <https://aerobasegroup.com/nsn/4720-00-009-2413>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

0.875 inches

**Temperature Rating:**

-65.0 degrees fahrenheit single response and 375.0 degrees fahrenheit single response

**Outside Diameter:**

1.156 inches

**Minimum Inside Bending Radius:**

5.500 inches

**Angle Between Rigid Elbow Fittings In Deg:**

52.0

**Center To Center Distance Between Bolt Holes Along Width:**

1.812 inches 1st end

**Center To Center Distance Between Bolt Holes Along Length:**

1.812 inches 1st end

**Bolt Hole Quantity:**

4 2nd end

**Flange Length:**

2.375 inches 1st end

**Flange Width:**

2.375 inches 1st end

**Connection Style:**

Plain swivel 2nd end

**Bolt Hole Diameter:**

0.266 inches 2nd end

**End Flange Construction:**

Split 2nd end

**End Connection Design:**

Elbow 2nd end

**Connection Type:**

Plain face flange 2nd end

**Features Provided:**

Electrostatic discharge capability

**Burst Test Pressure:**

2500.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

750.0 pounds per square inch

**Hydrostatic Test Pressure:**

1500.0 pounds per square inch

**Flow Angle:**

45.0 degrees 1st end

**Outer Covering Environmental Protection:**

Corrosion resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

21.625 inches working and 22.125 inches working

**Flange Style:**

Rectangular (includes square) 2nd end

**Special Features:**

Braided fire sleeve, non-asbestos

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Supplementary Features:**

This item has been reviewed for asbestos material; the current approved sources; 00624 have indicated their part number contained asbestos prior to 1984; they continue to manufacture the same part number without asbestos material after 1984

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0