

View Online at <https://aerobasegroup.com/nsn/4720-00-009-5242>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.250 inches

**Temperature Rating:**

-67.0 degrees fahrenheit and 212.0 degrees fahrenheit single response

**Outside Diameter:**

Between 0.535 inches and 0.573 inches

**Minimum Inside Bending Radius:**

1.000 inches

**Connection Style:**

Swivel nut flare 2nd end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Burst Test Pressure:**

6000.0 pounds per square inch

**Layer Composition And Location:**

2nd layer braided wire and outer layer rubber impregnated braided fabric and 1st layer braided fabric

**Maximum Operating Pressure:**

1500.0 pounds per square inch

**Thread Size:**

0.500 inches 2nd end

**Seat Angle:**

37.0 degrees 2nd end

**Hydrostatic Test Pressure:**

3000.0 pounds per square inch

**Flow Angle:**

45.0 degrees 2nd end

**Outer Covering Environmental Protection:**

Fuel resistant and mildew resistant and oil resistant and ozone resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

117.000 inches working

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Unf 2nd end

**Specification Data:**

81349-mil-h-13444 government specification

**Specification Or Standard:**

3 type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0

**Mil-std (military Standard):**

Mil-h-13444 spec.