

View Online at <https://aerobasegroup.com/nsn/4720-00-009-7237>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.750 inches

**Temperature Rating:**

-10.0 degrees fahrenheit and 175.0 degrees fahrenheit single response

**Outside Diameter:**

1.453 inches

**Minimum Inside Bending Radius:**

4.000 inches

**Exterior Color:**

Black

**Connection Style:**

Swivel nut flare 2nd end

**End Connection Design:**

Straight 2nd end

**Connection Type:**

Threaded internal tube 1st end

**Burst Test Pressure:**

600.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided polyamide cord and 1st layer braided wire

**Maximum Operating Pressure:**

150.0 pounds per square inch

**Thread Size:**

0.875 inches 2nd end

**Seat Angle:**

37.0 degrees 2nd end

**Hydrostatic Test Pressure:**

300.0 pounds per square inch

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

240.000 inches

**Special Features:**

Braided wire reinforcement molded to inner conveying tube

**Thread Series Designator:**

Unf 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0