## NSN 4720-00-009-7237

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-009-7237 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.750 inches **Tempurature Rating:** -10.0 degrees fahrenheit and 175.0 degrees fahrenheit single response **Outside Diameter:** 1.453 inches **Minimum Inside Bending Radius:** 4.000 inches **Exterior Color:** Black **Connection Style:** Swivel nut flare 2nd end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 600.0 pounds per square inch **Layer Composition And Location:** Outer layer braided polyamide cord and 1st layer braided wire **Maximum Operating Pressure:** 150.0 pounds per square inch **Thread Size:** 0.875 inches 2nd end Seat Angle: 37.0 degrees 2nd end **Hydrostatic Test Pressure:** 300.0 pounds per square inch **Inside Surface Condition:** Smooth **Measuring Method And Length:** 240.000 inches

**Special Features:** 

Braided wire reinforcement molded to inner conveying tube

**Thread Series Designator:** 

Unf 2nd end

## NSN 4720-00-009-7237

Nonmetallic Hose Assembly - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0